



# Plasterboard Alternatives

With the wide range of plasterboard types there are occasionally some overlaps in functionality. For situations not covered below contact the GIB® Helpline on 0800 100 442.

## Acceptable GIB® Standard Alternatives

10mm GIB® Standard can be replaced with	10mm GIB Braceline® / GIB Noiseline® 10mm GIB Fyreline® 10mm GIB Ultraline® 10mm GIB Aqualine®
13mm GIB® Standard can be replaced with	13mm GIB Braceline® / GIB Noiseline® 13mm GIB Fyreline® 13mm GIB Ultraline® 13mm GIB Aqualine® 13mm GIB Toughline® 13mm GIB Toughline® Aqua

## Acceptable GIB Fyreline® Alternatives

10mm GIB Fyreline® can be replaced with	10mm GIB Braceline® / GIB Noiseline® 10mm GIB Ultraline® 10mm GIB Aqualine® 13mm GIB® Standard
13mm GIB Fyreline® can be replaced with	13mm GIB Braceline® / GIB Noiseline® 13mm GIB Aqualine® 13mm GIB Toughline® 13mm GIB Toughline® Aqua

## Acceptable GIB Braceline® / GIB Noiseline® Alternatives

10mm GIB Braceline® / GIB Noiseline® can be replaced with:	10mm GIB Aqualine® (see Note 1) 13mm or thicker GIB Fyreline® (see Notes 1 & 2)
13mm GIB Braceline® / GIB Noiseline® can be replaced with:	13mm GIB Aqualine® (see Notes 1 & 3 below) 13mm or thicker GIB Fyreline® (see Notes 1, 2 & 3) 13mm GIB Toughline® (see Note 3) 13mm GIB Toughline® Aqua (see Note 3)

**Note 1:** The bracing element must be 900mm or greater in length. Fasteners to be at 100mm centres to the perimeter of the bracing element. Corner bracing fastener pattern applies. Hold downs required.

**Note 2:** Fastener type and length must be as specified for the relevant fire rated system.

**Note 3:** The bracing performance will be met but the noise control rating will be reduced.